



Triton® I

Triton® II

TRITON® & TRITON® II WITH CLEARPRO® TECHNOLOGY

THE FILTER THAT WILL OUTLIVE YOUR POOL ...

The **Triton®** sand filter is the result of over 40 years of product evolution and refinement. It has set the industry standard for effectiveness, efficiency, long runs between service and providing years of dependable, low maintenance operation. **Triton®** features a special internal design that keeps the sand bed level, ensuring even water flow and resulting in the most efficient filtration possible.

- Time-proven internal design ensures that all water receives maximum filtration for crystal clear results.
- One-piece, fiberglass-reinforced tank with a UV-resistant coating for years of dependable, corrosion-resistant service.
- Flow system design controls filtration quality and ensures maximum run times between backwashing to save you time.



NOW CAPABLE OF DELIVERING POOL WATER OF CRYSTAL QUALITY



Triton is now also available with **ClearPro Technology (Triton II version)** :

A patented technology to reach a very fine level of filtration, 4 times better than with a conventional sand filter. As a result the water is of crystal quality. ClearPro® approaches DE filter clarity with sand filter functionality. The secret is a component inside the filter - a porous tube through which water must pass before it re-enters the pool. It creates a final barrier to the small particles, including the finest dust particles, algae and pollens. At the same time, **Triton II** remains the blissfully simple filter that requires less maintenance than either cartridge or diatomaceous filters. Just an occasional backwashing with the turn of a valve is all it takes to keep **Triton II** delivering the clearest water year after year.

TRITON® & TRITON® II WITH CLEARPRO® TECHNOLOGY



Easy-to-read pressure gauge

6-way valve


One-piece fiberglass reinforced tank

KEEPING IT SIMPLE WHILE MAKING IT SPARKLE

Besides its superior filtration performance, the **Triton®** sand filter delivers a level of dependability and ease of operation and maintenance for a track record that's unsurpassed. Every design detail has been refined to make **Triton®** the industry standard.

ADDITIONAL FEATURES INCLUDE:

- Easy-to-use water drain for simplified service and winterizing.
- Easy connect to garden hose
- Easy access, heavy-duty closure with built-in pressure relief valve for fast, save en easy maintenance and inspection.
- All internal parts are threaded for ease of maintenance.
- Swing-away water diffuser allows instant access to sand and all internal parts.
- Maximum operating temperature 50°C.
- 10-year limited warranty (Shell only).



TRITON	TRITON II	Filter Diameter (mm)	Flow Rate (m³/h)	Filter Area (m²)
F-19S8-TRV	F-19S8-TRCP	480	8.5	0.17
F-24S8-TRV	F-24S8-TRCP	610	14	0.29
F-30S8-TRV	F-30S8-TRCP	762	22	0.45
F-36S8-TRV	F-36S8-TRCP	914	32	0.64



Customer support :

T 0032 14 25 99 11
F 0032 14 25 99 25
poolemea@pentair .com
www.pentairpooleurope.com

AVAILABLE FROM:

Copyright - Limited License: except as specifically permitted herein, no portion of the content on this document may be reproduced in any form or by any mean without the prior written permission of Pentair International SRL

[Automation / Filters / Filter Systems / Pumps / Heat Pumps / Cleaners / White Goods / Lighting / Sanitizers / Salt Chlorinators / Dosing and Measuring Equipment / Maintenance Accessories / Water Features](#)

NVA - BR - TR - EN © 2012 Pentair International SRL. All Rights Reserved. Rev. 03-2014.

