



→ 90 M³

TRITON[®] NEO TM


The improved version of the top-mount Industry standard.



FEATURES

- Same as Tagelus but
- 6w Top Mount Valve with Sight Glass, pressure gauge
- Max working pressure: 3.5 bars
- New metallic blue colour with shiny gloss, UV resistant
- Reinforced inner packaging

Available with ClearPro Technology[®]




TECHNICAL FEATURES & PRICE

Part number		Diameter Ø (mm)	Filter area (m ²)	Flow rate (m ³ /h)	Max pressure (bars)	Valve connection	Sand (kg) 0.4 - 0.8 mm	Gravel (kg) 3- 5 mm	Clearance distance (mm)	Valve	List Price (€ excl. VAT)	
Standard	ClearPro										Standard	ClearPro
F-19T6-NEO	F-19T6-NEOCP	480	0.17	8.5	3.5	1.5"	50	25	985	6 way	564	555
F-24T6-NEO	F-24T6-NEOCP	610	0.29	14	3.5	1.5"	100	50	1115	6 way	652	667
F-30T8-NEO	F-30T8-NEOCP	762	0.45	22	3.5	2"	200	75	1286	6 way	861	991

Valve included ⁽¹⁾ No gravel with Clearpro technology

DIMENSIONS



Part number	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)
F-19T6-NEO	878	400	Ø 480	715	774	1194
F-24T6-NEO	1009	400	Ø 610	847	904	1448
F-30T8-NEO	1170	610	Ø 762	1026	1108	1664

PACKAGING

Part number		Box				Pallet			
Standard	ClearPro	Length (mm)	Width (mm)	Height (mm)	Weight (kg)	Length (mm)	Width (mm)	Height (mm)	Pce/Pallet
F-19T6-NEO	F-19T6-NEOCP	49	49	88	11	98	98	189	8
F-24T6-NEO	F-24T6-NEOCP	63	63	102	16.3	126	126	218	8
F-30T8-NEO	F-30T8-NEOCP	78	78	120	28.3	156	80	134	2